

HICC-2600T

www.asia.security.honeywell.com

1080P High Definition H.264 IP Box Camera

Honeywell HICC-2600T combines world-class imaging and the latest IP camera technology with IP networking innovation, providing streaming images at full frame rate at 1080P resolution. With advanced resolution projection, the HICC-2600T delivers high quality images, making it an ideal solution for high-end surveillance applications.

Featuring H.264 high profile compression format, the HICC-2600T saves network bandwidth and storage even for continuous recording.

The HICC-2600T is equipped with built-in Power over Ethernet (IEEE 802.3af), which allows power to be supplied to the camera using the network, eliminating the need for a separate power supply and reducing the cost of installation. For additional installation flexibility, the HICC-2600T can also be powered with DC 12V and AC 24V.

Market Opportunities

Featuring 1080P high resolution, H.264 high profile compression format, PoE and ONVIF interface, the HICC-2600T optimizes surveillance performance for applications that require excellent image clarity and highdefinition imaging at minimal bandwidth. The camera is most suitable for advanced applications such as metro, banks, railways, financial institutes, government buildings, airports etc.

FEATURES

- 1080P high resolution
- H.264, and MJPEG simultaneously (Dual-encoders)
- H.264 high profile saves bandwidth and storage
- True Day/Night (with IR-cut filter)
- WDR, 3DNR, DC IRIS, and Anti-flicker
- Comprehensive I/O ports: audio in, audio out, video out, Alarm In, Alarm Out, RJ45, SD card slot, RS485 and USB
- Built in Power over Ethernet (PoE); 100Base-T Ethernet
- Event triggering camera tampering, Motion detection, Network loss, Alarm Input, Video loss
- Event trigger action SNAP, Record video in SD card slot, send to FTP, send to Email, External output activation, voice alert, notify to CMS
- Edge storage up to 32G
- Compatible with Honeywell Universal Surveillance (HUS) Platform and NVRs
- ONVIF Profile S compliant



Driving IP-based physical security through global standardization





HICC-2600T

www.asia.security.honeywell.com

1080P High Definition H.264 IP Box Camera

SPECIFICATIONS


Camera	HICC-2600T
mage Device	Sony 1/2.9" Exmor™ image sensor
Effective Pixels	1920 x 1080 pixels
ens Interface	CS/C
is	DC Iris
CR	Mechanical, TDN
<i>I</i> in. Illumination	Color: 0.02lux @ F1.4 (AGC ON) B/W: 0.005lux @ F1.4(AGC ON)
P Video	
/ideo Compression	H.264, and MJPEG simultaneously (Dual-encoders)
/ideo Profile	H.264 baseline, main, high profile
Profile Setting	Every video profile has independent CBR/ VBR/ GOP/ Frame rate setting
Aain Stream Resolution	1080P (1920 x 1080), 720P (1280 x 720), Q1080P (960 x 544)
Second Stream Resolution	720P (1280 x 720), Q1080P (960 x 544), D1 (720 x 576), VGA (640 x 480), Q720P (640 x 360) CIF (352 x 288), QVGA (320 x 240), QCIF (176 x 144)
rame Rate	1fps - 25/30fps
Bit Rate	16 - 8000kbps
Electronic Shutter	Auto mode: 1/25 - 1/30000 sec Manual mode: 1/25 - 1/10000 sec
is Exposure Control	Auto mode / Manual mode
AGC	LOW / MID-LOW / MID / MID-HIGH / HIGH
VDR	OFF / LOW / MID / HIGH
B-DNR	OFF / LOW / MID / HIGH
Color Mode	Normal / Natural / Bright
mage Setting	AE, AWB; 3D Noise reduction; WDR; Color, brightness, sharpness, contrast, Hue; Mirror/Flip Privacy Masks; Text, time and date overlay
Streaming	Simultaneously multi-profile streaming; Streaming over UDP, TCP, HTTP, or HTTPS; M-JPEC streaming over HTTP (server push); Controllable frame rate and bandwidth; Constant and variable bit rate (MPEG4 / H.264)
Dn Screen Display	Text, time and date overlay
Audio	
Audio Encoder	RTSP: G.711 64kbps
Audio Streaming	One-way or two-way
Audio Input	External audio in
Audio Output	Speaker Out
Jetwork	
Supported Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, FTP, NTP, DNS, DDNS, DHCP, ARP, Bonjour UPnP, RTSP, RTP, RTCP, IGMP, PPPoE, ICMP, SNMP
Security	Password protection, HTTPS encrypted data transmission, user access log
Jsers	4 simultaneous unicast users
Ethernet	10/100M auto negotiation
System Integration	
Supported Interface	ONVIF Profile S
Event Detection	Alarm in, motion detection, Network loss detection, camera tampering, Video loss
Notion Detection	1-zone video motion detection with Sensitivity options
Privacy Mask	4-Zone
Camera Tampering	Camera Cover or Mask
Events Action	SNAP, Record video in SD card, send to FTP, send to Email, External output activation, voice alert, notify to CMS
Aotion Detection Privacy Mask Camera Tampering	1-zone video motion detection with Sensitivity options 4-Zone Camera Cover or Mask SNAP, Record video in SD card, send to FTP, send to Email, External output activation

1080P High Definition H.264 IP Box Camera

Camera	HICC-2600T
General	
OS	Windows XP or later
Browser	IE 8.0 or later
Supported Platform	Honeywell Universal Surveillance (HUS) and NVRs
Power Supply	12V DC or 24V AC ±10% external power adapter
PoE	IEEE 802.3af
Power consumption	Max 4W
Connectors	RJ-45 10Base-T/100Base-TX; 1 power jack; 1 alarm input and 1 output; Audio out; Audio input; Video out; Factory default reset; SD card, USB and RS485
Edge Storage	32G
Operating Temperature	-20°C to 55°C
Operating Humidity	0% - 90% (non-condensing)
Dimensions	138 (L) x 58 (W) x 62 (H) mm
Weight	376g net
Certificate	CE, FCC, UL

Note: Honeywell reserves the right, without notification, to make changes in product design or specifications.

DIMENSIONS



Unit: mm

HICC-2600T

www.asia.security.honeywell.com

1080P High Definition H.264 IP Box Camera

ORDERING

HICC-2600T

1080P IP Box Camera, H.264 High-profile, TDN, WDR, ONVIF Profile S, Edge storage 32G, Tampering Detection , PoE, 24VAC/12VDC

For more information:

Security Asia Pacific Headquarters Security Australia Sales Hotline Security China Sales Hotline Security Hong Kong Security India

www.asia.security.honeywell.com security.ap@honeywell.com

Honeywell Security Group Honeywell International Inc. www.security.honeywell.com Tel: (86) 21 2219 6888 Tel: 1300 234 234 Tel: 400-8800-330 Tel: (852) 2405 2323 Tel: (91) 124 497 5000 Security Indonesia Security Korea Security Singapore Security Taiwan Security Thailand Tel: (62 21) 536 52322 Tel: (82) 2 799 6114 Tel: (65) 6355 2828 Tel: (886) 2 2245 1000 Tel: (66) 2 693 3099



Apr 2014 © 2014 Honeywell International Inc.