

HIDC-P-3100IRV

3 Megapixel H.264 Vari-Focal IR IP Fixed Dome

Honeywell Pioneer Series HIDC-P-3100IRV Megapixel network camera combines world-class imaging and leading IP camera technologies, providing streaming images in 3 Megapixel (2048 x 1536) and full HD (1920 x 1080) real-time frame rate. With such advanced resolution projection, the HIDC-P-3100V delivers ultra high image quality in any condition, making it an ideal choice for critical facilities to apply advanced surveillance standard.

The H.264 high profile compression format saves network bandwidth and storage for continuous recording. The 3 – 9mm vari-focal lens allows the field of view to be adjusted to match the scene requirements.

At low illumination or complete darkness, the HIDC-P-3100IRV uses 12 built-in IR LEDs to provide useable black and white video with a viewing range of up to 15m from the camera.

The HIDC-P-3100IRV is equipped with built-in Power over Ethernet (IEEE 802.3af), which allows power to be supplied to the camera using the network, eliminating the need for a separate power supply and reducing the cost of installation. For additional installation flexibility, the HIDC-P-3100IRV can also be powered with DC 12V and AC 24V.

Market Opportunities

Featuring 3 Megapixel image resolution, H.264 video compression, built-in IR LED, PoE and ONVIF interface, the HIDC-P-3100IRV optimizes surveillance performance for applications that require excellent image clarity and high-definition imaging at minimal bandwidth. It meets the high standard requirements for critical facilities such as metro, banks, railway, financial institutes, government buildings, airports etc.

FEATURES

- 3 Megapixel resolution at 25/30fps
- H.264 (high profile / main profile / baseline) and MJPEG simultaneously
- Built in IR LED
- True Day/Night
- Comprehensive I/O ports: MIC in, audio out, video out, DI, DO, RS485, RJ45, mSD
- Built in Power over Ethernet (PoE); Gigabit (1000Base-T) Ethernet
- Support various protocols: RTSP, UPnP, 3GPP, HTTPS, Samba
- Event trigger action: Send to NAS, send to FTP, send to Email, voice alert, go preset and tour, notify to
- Compatible with Honeywell Universal Surveillance (HUS) Platform and NVRs
- ONVIF compliant



Driving IP-based physical security through global standardization

HIDC-P-3100IRV

www.asia.security.honeywell.com

3 Megapixel H.264 Vari-Focal IR IP Fixed Dome

SPECIFICATIONS

| | |
|---------------------|--|
| Model | HIDC-P-3100IRV |
| Camera | |
| Image Device | 1/2.8" Sony progressive scan Exmor 3.4 Megapixel CMOS image sensor |
| Effective Pixels | 2096 x 1561 (3 Megapixel) |
| Lens | 3 - 9mm vari-focal lens |
| Min. Illumination | Color: 0.2 lux @ F1.2 / B/W: 0.08 lux |
| Day & Night | TDN (Auto ICR) |
| Illumination LED | 12 IR LEDs |
| IR Distance | 10 - 15m |
| IR LED Control | Auto (Photo Sensor Mode) IR LED ON when less than 15 Lux Manual: User Programmable |
| Video | |
| Video Compression | H.264 (hi-profile, main-profile, baseline) and MJPEG simultaneously |
| Video Profile | <ul style="list-style-type: none"> · 3 Megapixel Mode (H.264 and MJPEG) – 2048 x 1536; 1280 x 960; 640 x 480; 320 x 240 · Full HD Mode (H.264 & MJPEG) – 1920 x 1080; 1280 x 720; 640 x 360; 320 x 180 · Dual Streams – H.264 2048 x 1536 (30fps) + H.264 2048 x 1536 (30fps) · Triple Streams – H.264 1920x1080(30fps) x 2 + H.264 1280x720 (30fps) |
| Frame Rate | Up to 25/30fps in all resolutions |
| Region of Interest | Max. 2 ROI @ 3M mode. Editable range Max. 3 ROI @ 1080P mode. Editable range |
| Image Setting | BLC, AGC, AE, AWB; 3D Noise reduction; WDR; Color, brightness, sharpness, contrast, Hue; Image Mirror/Flip; Privacy Masks: 7 areas |
| Streaming | Simultaneously multi-profile streaming; Streaming over UDP, TCP, HTTP, or HTTPS; M-JPEG streaming over HTTP (server push); Controllable frame rate and bandwidth; Constant and variable bit rate; ROI |
| On Screen Display | Text, time and date overlay; Editable OSD |
| Language | English, Traditional Chinese, Simplified Chinese, Korean |
| Audio | |
| Audio Encoder | RTSP: G.711 64kbps, G.726 32kbps |
| Audio Streaming | One-way or two-way |
| Microphone | External microphone |
| Audio Output | Adjustable audio output gain |
| Network | |
| Supported Protocols | IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, FTP, NTP, DNS, DDNS, DHCP, DIPS, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, IGMP, PPPoE, 3GPP, Samba, ICMP |
| Security | Password protection, IP address filtering, HTTPS encrypted data transmission, user access log |
| Users | 8 simultaneous unicast users |
| Ethernet | 10Base-T/100Base-TX/1000Base-T auto negotiation |

HIDC-P-3100IRV

www.asia.security.honeywell.com

3 Megapixel H.264 Vari-Focal IR IP Fixed Dome

SPECIFICATIONS

| | |
|-------------------------|--|
| Model | HIDC-P-3100IRV |
| System Interface | |
| Supported Interface | ONVIF |
| Alarm Triggers | Intelligent video motion detection; Camera Tampering; Audio Detection; Digital input |
| Motion Detection | 10-zone video motion detection with included or excluded options |
| Alarm Events | File upload via FTP or email; File upload via Samba to NAS; Notification via email, HTTP, and TCP; External output activation; Audio alerting output; Micro SD card local storage |
| Video Buffer | Pre- and post- alarm buffering |
| Viewing System | |
| Browser | IE 8.0 or later |
| Platform | |
| Supported Platform | Honeywell Universal Surveillance (HUS) and NVR |
| General | |
| Power Supply | 12V DC or 24V AC |
| Power Consumption | 10W (12VDC) |
| PoE | IEEE 802.3af Class 3 |
| Connectors | RJ-45 10Base-T/100Base-TX/1000Base-T; 12VDC power jack; AC24V terminal; 1 alarm input and 1 output; RS485; Audio out; External MIC input; Compositing video out; Factory default reset; mSD card |
| Indication LED | Green and orange LEDs |
| Operating Temperature | -10°C to 50°C |
| Operating Humidity | 10% - 90% (non-condensing) |
| Dimensions | 151.37 (D) mm x 108.95 mm |
| Weight | 595g |
| Certificate | CE, FCC |

Note: Honeywell reserves the right, without notification, to make changes in product design or specifications.

ORDERING

| | |
|----------------|--|
| HIDC-P-3100IRV | IP IR Dome Camera. 3 Megapixel @ 25/30fps. 3 – 9mm vari-focal. IR beam distance 10 – 15m. H.264 High Profile. TDN. PoE, 24VAC/12VDC. ONVIF |
|----------------|--|

HIDC-P-3100IRV

www.asia.security.honeywell.com

3 Megapixel H.264 Vari-Focal IR IP Fixed Dome

For more information:

Security Asia Pacific Headquarters
Security Australia Sales Hotline
Security China Sales Hotline
Security Hong Kong
Security India

Tel: (86) 21 2219 6888
Tel: 1300 234 234
Tel: 400-8800-330
Tel: (852) 2405 2323
Tel: (91) 124 497 5000

Security Indonesia
Security Korea
Security Singapore
Security Taiwan
Security Thailand

Tel: (62 21) 536 52322
Tel: (82) 2 799 6114
Tel: (65) 6355 2828
Tel: (886) 2 2245 1000
Tel: (66) 2 693 3099

www.asia.security.honeywell.com
security.ap@honeywell.com

Honeywell Security Group
Automation & Control Solutions
Honeywell International Inc.
www.security.honeywell.com

Nov 2013
© 2013 Honeywell International Inc.

Honeywell