

## HIVDC-P-3100IRV

www.asia.security.honeywell.com

### 3 Megapixel High Definition H.264 Vari-Focal IP Vandal-Proof Fixed Dome

Honeywell Hera Series HIVDC-P-3100IRV Megapixel network camera combines world-class imaging and leading IP camera technologies, providing streaming images in 3 Megapixel (2048 x 1536) and full HD (1920 x 1080) real-time frame rate. With such advanced resolution projection, the HIVDC-P-3100IRV delivers ultra high image quality in any condition, making it an ideal choice for critical facilities to apply advanced surveillance standard.

The H.264 high profile compression format saves network bandwidth and storage for continuous recording. The 3 – 9mm vari-focal lens allows the field of view to be adjusted to match the scene requirements. At low illumination or complete darkness, the HIVDC-P-3100IRV uses 12 built-in LEDs to provide useable black and white video with a viewing range of up to 15m from the camera. Equipped with IP66 housing, the HIVDC-P-3100IRV is vandal-proof and weatherproof that can be installed in any outdoor applications.

The HIVDC-P-3100IRV is equipped with built-in Power over Ethernet (IEEE 802.3af), which allows power to be supplied to the camera using the network, eliminating the need for a separate power supply and reducing the cost of installation. For additional installation flexibility, the HIVDC-P-3100IRV can also be powered with DC 12V and AC 24V.

#### Market Opportunities

Featuring 3 Megapixel image resolution, H.264 video compression, IR, PoE and ONVIF interface, the HIVDC-P-3100IRV vandal-proof camera optimizes surveillance performance for applications that require excellent image clarity and high-definition imaging at minimal bandwidth. It meets the high standard requirements for critical facilities such as metro, banks, railway, financial institutes, government buildings, airports etc.

#### FEATURES

- 3 Megapixel resolution at 25/30fps
- H.264 high profile – saves bandwidth and storage
- Region of Interest (ROI)
- Built-in IR LED
- True Day/Night
- Built in Power over Ethernet (PoE); Gigabit (1000Base-T) Ethernet
- Comprehensive I/O ports: MIC in, audio out, video out, DI, DO, RS485, RJ45, mSD
- Event trigger action: Send to NAS, send to FTP, send to Email, voice alert, notify to HTTP/TCP servers
- IP66, vandal-proof
- Compatible with Honeywell Universal Surveillance (HUS) Platform and NVRs
- ONVIF compliant



Driving IP-based physical security through global standardization

# HIVDC-P-3100IRV

www.asia.security.honeywell.com

## 3 Megapixel High Definition H.264 Vari-Focal IP Vandal-Proof Fixed Dome

### SPECIFICATIONS

Model	HIVDC-P-3100IRV
<b>Camera</b>	
Image Device	1/2.8" Sony progressive scan Exmor 3.4 Megapixel CMOS image sensor
Effective Pixels	2096 x 1561 (3 Megapixel)
Lens	3 - 9mm vari-focal lens
Min. Illumination	Color: 0.2 lux @ F1.2 / B/W: 0.08 lux
Day/Night	TDN (Auto ICR)
IR LED Control	IR LED ON when less than 15 Lux
IR LED	12 IR LEDs
IR Beam Distance	15m
<b>Video</b>	
Video Compression	H.264 (hi-profile, main-profile, baseline) and MJPEG simultaneously
Video Profile	<ul style="list-style-type: none"> <li>· 3 Megapixel Mode (H.264 and MJPEG) – 2048 x 1536; 1280 x 960; 640 x 480; 320 x 240</li> <li>· Full HD Mode (H.264 &amp; MJPEG) – 1920 x 1080; 1280 x 720; 640 x 360; 320 x 180</li> <li>· Dual Streams – H.264 2048 x 1536 (30fps) + H.264 2048 x 1536 (30fps)</li> <li>· Triple Streams – H.264 1920x1080(30fps) x 2 + H.264 1280x720 (30fps)</li> </ul>
Frame Rate	Up to 25/30fps in all resolutions
Region of Interest	Max. 2 ROI @ 3M mode. Editable range Max. 3 ROI @ 1080P mode. Editable range
Image Setting	BLC, AGC, AE, AWB; 3D Noise reduction; WDR; Color, brightness, sharpness, contrast, Hue; Image Mirror/Flip; Privacy Masks: 7 areas
Streaming	Simultaneously multi-profile streaming; Streaming over UDP, TCP, HTTP, or HTTPS; M-JPEG streaming over HTTP (server push); Controllable frame rate and bandwidth; Constant and variable bit rate; ROI
On Screen Display	Text, time and date overlay; Editable OSD
Language	English, Traditional Chinese, Simplified Chinese, Korean
<b>Audio</b>	
Audio Encoder	RTSP: G.711 64kbps, G.726 32kbps
Audio Streaming	One-way or two-way
Microphone	External microphone
Audio Output	Adjustable audio output gain
<b>Network</b>	
Supported Protocols	IPv4, IPv6, TCP, UDP, HTTP, HTTPS, SMTP, FTP, NTP, DNS, DDNS, DHCP, DIPS, ARP, Bonjour, UPnP, RTSP, RTP, RTCP, IGMP, PPPoE, 3GPP, Samba, ICMP
Security	Password protection, IP address filtering, HTTPS encrypted data transmission, user access log
Users	8 simultaneous unicast users
Ethernet	10Base-T/100Base-TX/1000Base-T auto negotiation

# HIVDC-P-3100IRV

www.asia.security.honeywell.com

## 3 Megapixel High Definition H.264 Vari-Focal IP Vandal-Proof Fixed Dome

### SPECIFICATIONS

Model	HIVDC-P-3100IRV
<b>System Integration</b>	
Supported Protocols	ONVIF
Alarm Triggers	Intelligent video motion detection; Camera Tampering; Audio Detection; Digital input
Motion Detection	10-zone video motion detection with included or excluded options
Alarm Events	File upload via FTP or email; File upload via Samba to NAS; Notification via email, HTTP, and TCP; External output activation; Audio alerting output; Micro SD card local storage
Video Buffer	Pre- and post- alarm buffering
<b>Viewing System</b>	
Browser	IE 8.0 or later
<b>Platform</b>	
Supported Platform	Honeywell Universal Surveillance (HUS) and NVR
<b>General</b>	
Power Supply	12V DC or 24V AC
Power Consumption	10W (12 VDC)
PoE	IEEE 802.3af Class 3
Connectors	RJ-45 10Base-T/100Base-TX/1000Base-T; 12VDC power jack; AC24V terminal; 1 alarm input and 1 output; RS485; Audio out; External MIC input; Compositing video out; Factory default reset; mSD card
Protection	IP66, vandal-proof
Operating Temperature	-20°C to 60°C
Operating Humidity	10% - 90% (non-condensing)
Dimensions	139.95(D) x 131.17(H) mm
Weight	1015g
Certificate	CE, FCC

Note: Honeywell reserves the right, without notification, to make changes in product design or specifications.

### ORDERING

HIVDC-P-3100IRV	IP IR Vandal-Proof Dome Camera. 3 Megapixel @ 30fps. 3 – 9mm vari-focal. IR beam distance 15m. H.264 High Profile. TDN. PoE, 24VAC/12VDC. ONVIF
-----------------	---

## HIVDC-P-3100IRV

[www.asia.security.honeywell.com](http://www.asia.security.honeywell.com)

---

### 3 Megapixel High Definition H.264 Vari-Focal IP Vandal-Proof Fixed Dome

For more information:

Security Asia Pacific Headquarters  
Security Australia Sales Hotline  
Security China Sales Hotline  
Security Hong Kong  
Security India

Tel: (86) 21 2219 6888  
Tel: 1300 234 234  
Tel: 400-8800-330  
Tel: (852) 2405 2323  
Tel: (91) 124 497 5000

Security Indonesia  
Security Korea  
Security Singapore  
Security Taiwan  
Security Thailand

Tel: (62 21) 536 52322  
Tel: (82) 2 799 6114  
Tel: (65) 6355 2828  
Tel: (886) 2 2245 1000  
Tel: (66) 2 693 3099

[www.asia.security.honeywell.com](http://www.asia.security.honeywell.com)  
[security.ap@honeywell.com](mailto:security.ap@honeywell.com)

**Honeywell Security Group**  
Automation & Control Solutions  
Honeywell International Inc.  
[www.security.honeywell.com](http://www.security.honeywell.com)

Nov 2013  
© 2013 Honeywell International Inc.